

Design Advisory

From Kristin Schuster, Engineer of Design

MDOT
Design Division
PO Box 30050
Lansing, MI 48909
Phone/517-373-0030
Fax/517-241-4619
www.michigan.gov/mdot

Index:
FUSPs 12SP811F and
12SP812P, Pavement
Marking Standard
PAVE-900-E

*This advisory is
superseded by any
subsequent revisions to
the references listed in
this index.*

Questions regarding this
Design Advisory should
be directed to:

Mary Bramble
Design Programs
Phone 517-335-2837
BrambleM1@michigan.gov

Kimberly Ault
Design Programs
Phone 517-373-3340
AultK@michigan.gov



Use of Pavement Marking Removal and Recessing Pay Items

Pavement Marking and Cure Removal Pay Items

- “Rem Spec Mrkg” and “Rem Curing Compound, for Spec Mrkg”
 - Units of measurement: **Square Foot**
 - Symbol and legend areas located on PAVE-900
 - For removing all special or transverse markings, or removing the curing compound from new concrete ahead of surface-applied special or transverse marking placement
 - Includes:
 - Symbols
 - Legends
 - **Stop Bars**
 - **Crosswalks**
 - **Cross Hatching**
 - **Turning Guide Lines**
 - Optical Speed Bars
 - Roundabout Yield Lines (12” wide, 3’ mark 3’ gap)
 - Other markings not covered under longitudinal
- “Pavt Mrkg, Longit, __, Rem”
 - Unit of measurement: Foot
 - Separated pay items by width (6” or less, >6”)
 - Used for most removals
 - For removal of lane lines, edgelines, centerlines, and gore markings only
- “Pavt Mrkg, Longit, Water Blasting, __, Rem”
 - Unit of measurement: Foot
 - Separated pay items by width (6” or less, >6”)
 - Used for removals on concrete surfaces that will remain in place
 - For removal of lane lines, edgelines, centerlines, and gore markings only
- “Rem Curing Compound, for Longit Mrkg, __ inch”
 - Unit of measurement: Foot
 - Separated pay items by width of longitudinal pavement marking to be placed
 - Used for removing curing compound from new concrete ahead of surface-applied pavement markings
 - For removal of lane lines, edgelines, centerlines, and gore markings only

Design Advisory

DA 2016-06
Page 2
May 1, 2016

From Kristin Schuster, Engineer of Design

Pavement Marking Recessing Pay Items

- “Recessing Pavement Markings, Longit”
 - Unit of measurement: Foot
 - Not dependent on marking width
 - For recessing lane lines, edgelines, centerlines, and gore markings only

- “Recessing Pavement Markings, Transv”
 - Unit of measurement: Square Foot
 - Symbol and legend areas located on PAVE-900
 - For recessing all special markings except turning guide lines
 - Includes:
 - Symbols
 - Legends
 - **Stop Bars**
 - **Crosswalks**
 - **Cross Hatching**
 - Optical Speed Bars
 - Roundabout Yield Lines (12” wide, 3’ mark 3’ gap)
 - Other markings not covered under longitudinal

- “Recessing Pavt Mrkg, Turning Guide Line”
 - Unit of measurement: **Square Foot**
 - Quantity is affected by marking width
 - For recessing “turning blips” or other lane line extensions at intersections